

integra e

water purification units to provide
(s)htm 2030 quality water for use
with endoscope washing machines



- Suitable for supplying purified water to single or multi chamber endoscope washing machines
- Fully compliant with (S)HTM 2030, NHS MES C32 and the latest draft prEN ISO 15883 standards
- Integrated data logging for performance traceability
- Self contained
- Delivered factory tested for ease of installation
- Graphic displays for access to system parameters



integra e^h and e^s

water purification units to provide (s)htm 2030 quality water for use with endoscope washing machines

description

The Integra E unit is designed to take potable feedwater direct from the mains, purify it using Reverse Osmosis technology, store it in an integral storage tank and then circulate it via a pressurised ringmain to feed Endoscope Washing machines.

It is available in 2 versions tailored to the feedwater. The Integra E^H is for hard feedwater and the Integra E^S is for softened feedwater.

technical specification

Technical Data	Integra E ^S	Integra E ^H
Output @ 10°C (l/hr)	600	225
Feedwater hardness (ppm CaCO ₃)	< 4	400*
Feedwater temperature [°C]	1-35	1-35
Feedwater pressure [bar]	1-6	1-6
Pure water recovery (max %)	70	25
Feedwater consumption (max l/hr)	900	900
Pure water tank volume (l)	250	250
Drain flowrate	300	675
Power requirements	240V / 50Hz	240V / 50Hz
Width (mm)	1000	1000
Depth (mm)	750	750
Height (mm)	1800	1800

*For harder water a SUEZ water softener is required

unit design

Integral pure water tank – Ensures water is always available on demand. Tank is fully drainable and bacterially protected to comply with (S)HTM 2030.

Integral raw water break tank with Type AB air gap – Eliminates the possibility of water backflow and complies with water bylaws.

Self contained unit design – All components are integrated into a neat housing, designed to fit through standard sized doors and on wheels for enhanced portability.

Minimal installation and commissioning – All components are factory tested ensuring the unit simply requires connection to relevant on site services.

Semi-automatic chemical clean – With automatic chemical draw, recirculation and rinse, cleaning is straight forward and trouble free.

Bio Sample Point – Incorporation of a hygienic, fully sanitisable, stainless steel, sample valve reduces the risk of contamination during sampling.

Alarm conditions – Critical operating parameters are automatically monitored, including the quality of the purified water and level in the pure water tank.

User friendly display – Backlit display clearly shows the unit operation in graphic and text formats.

Standby mode – During periods of low demand the system will compensate, reducing power consumption and running costs

Integrated data logging – Up to 12 months data can be captured, enabling a permanent printed record of all parameter and status changes, in line with Good Manufacturing Practice (GMP).

contact

SUEZ Water Purification Systems Ltd
Bandet Way, Thame, Oxon OX9 3SJ

Tel: +44 (0)1844 217141 | Fax: +44 (0)1844 218098
Email: info@sueztreatmentsolutions.co.uk
Web: www.sueztreatmentsolutions.co.uk

