

prestige descale

high quality reverse osmosis units



- Compact, integrated water purifier
- Output options within the range include 1000, 2000, 4000 and 6000 litres per day
- Integrated pre-filtration
- Easy to install and maintain
- Graphical user interface
- Removes up to 98% of dissolved minerals
- Removes up to 99% of bacteria, colloids and organic contaminants



prestige descale - 1000-6000 litres per day

description

5µm pre-filter: Protects reverse osmosis (RO) membrane from fouling by particulates and colloidal contaminants found in mains water.

Internal break tank: Protects against feedwater pressure fluctuations and allows easy cleaning.

Integral boost pump: Enables RO membranes to operate at optimum performance.

Permeate divert: Ensures consistent permeate quality.

RO membrane: Removes up to 98% of dissolved minerals, and up to 99% of organic, bacterial and particulate contaminants.

Automatic membrane concentrate flush: Extends membrane life.

Product control selection: Allows continuous running or control via external tank level sensors.

technical specification

		PD50	PD100	PD150	PD250
Output	@ 25°C (l/hr)	70	146	291	430
	@ 10°C (l/hr)	42	84	168	250
Feedwater Hardness (Max) ¹ (ppm CaCO ₃)		20	20	20	20
Feedwater Temperature (Min / Max)		1°C / 35°C	1°C / 35°C	1°C / 35°C	1°C / 35°C
Feedwater Pressure (Min /Max)		2 bar / 6 bar	2 bar / 6 bar	2 bar / 6 bar	2 bar / 6 bar
Free Chlorine (ppm Cl ₂)		<0.1	<0.1	<0.1	<0.1
Optional Pretreatment Cylinder ²		AC7	AC7	AC8	AC8
Pure water recovery (Max %)		66	66	66	66
Feedwater consumption (Max l/hr)		106	221	441	651
Drain flowrate (Max l/hr)		36	75	150	221
Power requirements		100-230v/50-60hz	100-230v/50-60hz	100-230v/50-60hz	100-230v/50-60hz
Dimensions (w, d, h)		420mm x 548mm x 860mm	420mm x 548mm x 860mm	420mm x 548mm x 860mm	420mm x 548mm x 860mm
Weight (Working)		64 kg	64 kg	66 kg	66 kg
Weight (Shipping)		54 kg	54 kg	56 kg	56 kg

¹ For harder water a SUEZ water softener is required

² Optional pre-treatment required if free chlorine >0.1ppm or feedwater has a fouling index >5.

The unit is designed for a maximum TDS of 1000 mg/l, and a maximum colloidal index of 3. The permeate recovery depends on the raw water quality and the type of pretreatment.

contact

SUEZ Water Purification Systems Ltd
Bandet Way, Thame, Oxon OX9 3SJ

Tel: +44 (0)1844 217141 | Fax: +44 (0)1844 218098

Email: info@sueztreatmentsolutions.co.uk

Web: www.sueztreatmentsolutions.co.uk

